


SPECIFICATION

SXL General Purpose Cross(X) Linked Polyolefin Insulated Wires



SAE-J1128 Series

- Rated Temperature: 125°C
- Rated Voltage: 25 VAC and 60 VDC
- Reference Standard: SAE-J1128、ISO6722
- Stranded Tinned or Bare Copper Conductor
- XLPE Insulation
- No Marking

Application

For internal wiring of vehicles metres circuits and electronic equipments where exposed to temperatures not exceeding 125°C

Style	Conductor			Insulation		Over Diameter	Withstand Voltage KV	Packing
	AWG	MMSQ	No./AWG	Std.Thick mm	Min.Thick mm	Max mm		
SXL	22	0.35	7/30	0.74	0.52	2.2±0.1	1KV/Min	/
	20	0.5	7/28	0.74	0.52	2.8±0.1		/
	18	0.8	16/30	0.76	0.53	3.0±0.1		/
	16	1	26/30	0.81	0.57	3.4±0.1		/
	14	2	41/30	0.89	0.62	3.9±0.1		/
	12	3	65/30	0.94	0.66	4.6±0.1		/
	10	5	105/30	1.04	0.73	5.3±0.1		/
	8	8	168/30	1.09	0.76	6.2±0.1		/

Conductor tolerance: +/-0.008mm。

Specification available: Reference to specification table, special Specification also can be ordered。